

PRODUCT SPECIFICATIONS

SC2-250 HIGH SPEED
STRAIGHT SIDE DOUBLE CRANK



TECHNICAL DATA



	MEASUREMENTS
Press Tonnage (US Tons/kN)	275/2500
Tonnage Rating (in./mm)	.15/4
Slide Stroke (in./mm)	7.08/180
Press Speed (spm)	30-60
Stroke Down Adjust Up (in./mm)	23.03/585
Slide Adjustment (in./mm)	4.7/120
Upright Openings T-B (in./mm)	23.6/600
Upright Openings L-R (in./mm)	94.5/2400
Slide Area (in./mm)	78.7x27.6/2000x700
Bolster Area (in./mm)	90.6x36.2/2300x920
Main Motor (HP/KW)	40/30
Overall Dimensions (in./mm)	104.3x131.9x192.9/2650x3350x4900
Total Weight (US Tons /Ton)	42/38

- American brand controls
- Fast acting hydraulic overload system
- High rigidity steel welded frame
- Eight point long gibs
- Increased tool life, minimum deflection
- High off center load capability
- Parts and services from BCN Technical Services

Contact

Bliss Press USA
1004 East State Street
Hastings, Michigan 49058 | USA
P (888) 554-0325
info@blisspressusa.com
www.blisspressusa.com